



**TRUSTED, ACCURATE AND
RELIABLE!**

**The most comprehensive IT certification
preparation materials in the industry!**

All rights reserved. No part of this document may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of the publisher, except in the case of brief quotations embodied in critical reviews and certain other non-commercial uses permitted by copyright law. Unauthorized copying, reselling, or distribution of this document is strictly prohibited and may result in legal action.

<https://www.virtulearner.com>
support@virtulearner.com

Huawei

H12-425_V2.0

HCIP-Data Center Facility

Deployment V2.0

Certification Exam

QUESTION: 1

Which air supply mode requires reasonable raised floor height?

- A. Air supply mode using blast caps.
- B. Underfloor air supply mode
- C. Air supply mode using wind pipe
- D. In-row horizontal air supply mode

Answer(s): B

QUESTION: 2

Which of the following statements is true about UPS5000 power modules and bypass modules?

- A. The UPSS000-E-200K and UPS5000-E-400K use the same power module and provide the same capacity of 50 kVA but have different numbers of power modules.
- B. For UPSs of the same model but in different power segments, their bypass module capacity is the same.
- C. The power module capacity of both the UPS5000-S and UPS5000-E is 50 kVA. Therefore, the two types of UPS can be used together.
- D. The power modules used in the UPSS000-S-1200K are the same as those used in the UPS5000-E- 200K.

Answer(s): A

QUESTION: 3

In operant conditioning, the subject is free to make responses at any time, So conditioning is measured by the rate of responding. In most other Ways, however, their forms of learning are essentially the same.

- A. When UPSs are connected in parallel, connect loads to the pL terminal.
- B. When a single UPS works and loads are of the same importance, connect all loads to the sL terminal.
- C. When a single UPS works and loads are divided into two levels, connect the primary load to the sL terminal and the secondary load to the pl_ terminal.
- D. When the UPS is overloaded, the loads connected to the sL terminal will be powered off first to ensure continuous power supply to the loads connected to the pj_ terminal.

Answer(s): D

QUESTION: 4

What is the input/output voltage range of the SmartLi BCU?

- A. 280415 V
- B. 300400 V
- C. 300480 V
- D. W00-544 V

Answer(s): C

QUESTION: 5

To determine whether the R410A refrigerant meets requirements, compare the internal pressure of the refrigerant with the saturation pressure corresponding to the refrigerant temperature. If the difference between the internal pressure and the saturation pressure is within the range of which of the following, replace the refrigerant?

- A. 0-0.05 MPa
- B. 0.05-0.1 MPa
- C. 0.1-0.2 MPa
- D. 0.25-0.3 MPa

Answer(s): B

QUESTION: 6

Which of the following statements is false about the ECM of the UPS5000-E?

- A. As a control interface for the entire system, the ECM communicates with each module and provides a bus for communication between the dry contact card and the system control card.
- B. The ECM controls the bypass module to work properly, if one ECM is faulty, the UPS can still work in normal mode but cannot be manually switched to bypass mode.
- C. The ECM ensures equalized output currents between modules so that load power is equally shared.
- D. The ECM provides three types of CAN communication: monitoring CAN communication, intra-rack parallel CAN communication, and inter-rack parallel CAN communication.

Answer(s): B

QUESTION: 7

Due to simple operations and easy interconnection, which of the following communication types is recommended for NetEco northbound integration?

- A. WebService
- B. SNMP
- C. FTP
- D. PoE

Answer(s): A

QUESTION: 8

Which of the following PH values meets the water quality requirements of NetCol8000-E220?

- A. 3
- B. 5
- C. 7
- D. 9

Answer(s): C

QUESTION: 9